


B601

EDGE TRIMMER

Router for simultaneous flush trimming of top and bottom overhang of all edging materials, i.e. PVC, ABS, Melamine and natural wood veneers. (Floor Model) This machine is the ideal addition to our Model B 500K.





BASIC FEATURES

The two vertically mounted H.F. 0.35 kW router motors with variable speed between 4.000 and 18.000 RPM are equipped with R=3 mm x 4 wing throw-away tip type trimming cutters (standard). Other size radius and chamfer cutters can be supplied. Central Extraction pipe 100 mm Ø, 2 swarf extraction hoods with hose Ø 60 mm.

Digital adjustment of workpiece thickness

Technical Data

Workpiece width	min. ca. 30 mm
Edging thickness	0,4 – 3,0 mm
Electrical connection	230V, 50Hz, 1Ph
Total load	0,7 kW
Weight – nett	ca.100 kg
Workpiece thickness (rounding over)	approx. 16 – 55 mm
Workpiece thickness (chamfering)	approx. 12 – 55 mm
Internal radius	min. approx. 50 mm
Space required	approx. 810 x 610 x 885 mm



Lange Maschinenbau GmbH & Co. KG
Bruchweg 33 . D-32609 Hüllhorst
Tel: +49 (0) 57 44 - 45 75
Fax: +49 (0) 57 44 - 32 20
info@lange-maschinenbau.de
www.lange-maschinenbau.de

The technical data is a guide line only – our products are being constantly updated and we reserve the right to alter specifications, therefore the illustrations may vary from the actual machines from time to time. We reserve the right to alter the construction of our machines.